LING WAREHOUSE LADDERS

S O U T H W E S T **S O L U T I O N S** G R O U P

business efficiency systems

www.southwestsolutions.com

Toll Free 1-800-803-1083

Louisville Ladder steel rolling warehouse ladders are considered one of the best on the market. Ladder equipped with ball bearing casters allowing easy movement to any area. Rugged all steel construction. Sturdy handrails, easy 56 degree climbing angle, "Sure Grip" tread, 7" deep steps and 10" deep top platform provide quality features for the everyday user.

OR EXCEED THE REQUIREMENTS OF ANSI A14.7 AND OSHA 1910.29 STANDARDS WITH A 350 LB。 (standard on 2-step to 5-step





models) Four spring loaded casters on 2-5 step models. Casters retract

when load is placed on the ladder,

setting the ladder firmly in place

on rubber tips. When the load is removed, springs push down the

casters enabling the ladder to

move about freely.





Locking Device (standard on 6-step to 15-step models) Models 6-step and taller come equipped with a large 4' swivel caster in front and rigid casters in the rear. Stepping on bottom step activates the locking mechanism, locking rubber tipped feet in down position. To move the ladder, just step on the unlocking pedal.

NEW LLG MODEL	STEPS	STEP WIDTH	PLATFORM HEIGHT	OVERALL HEIGHT	OVERALL DEPTH	OVERALL WIDTH	APPROX. CUBE	WEIGHT	
NO HANDRAILS									
GSW1601A	1	16"	12"	12"	17"	19"	2.24	16	
GSW1601-W04	1	16"	12"	12"	17"	19"	2.24	16	
GSW1602	2	16"	20"	20"	19"	20"	6.66	25	
GSW2402	2	24"	20"	20"	19"	28"	8.33	30	
GSW2403	3	24"	30"	30"	27"	28"	13.54	41	
GSW1604	4	16"	40"	40"	35"	23"	18.05	47	
GSW2404	4	24"	40"	40"	35"	31"	20.83	55	
HANDRAILS									
GSW1603A	3	16"	30"	30"	27"	20"	13.54	46	
GSW2403-W03	3	24"	30"	66"	27"	28"	32.29	56	
GSW1604-W03	4	16"	40"	76"	35"	23"	30.00	58	
GSW2404-W03	4	24"	40"	76"	35"	31"	40.00	66	
GSW1605	5	16"	50"	86"	42"	23"	34.16	67	
GSW2405	5	24"	50"	86"	42"	31"	45.55	79	
GSW2406	6	24"	60"	96"	50"	34"	51.11	109	
GSW2407	7	24"	70"	106"	57"	34"	56.66	121	
GSW2408	8	24"	80"	116"	63"	34"	62.22	151	
GSW2409	9	24"	90"	126"	70"	34"	67.77	170	
GSW2410	10	24"	100"	136"	77"	34"	73.33	198	
GSW2411	11	24"	110"	146"	83"	34"	78.88	214	
GSW2412	12	24"	120"	156"	90"	34"	84.44	228	
GSW2413	13	24"	130"	166"	97"	39"	92.22	289	
GSW2414	14	24"	140"	176"	104"	39"	97.77	298	
GSW2415	15	24"	150"	186"	110"	39"	103.33	311	



No Forward Descent

56 degree climbing angle does not meet ANSI requirements for forward descent.



Premium Powder Paint Baked-on finish is durable and provides superior scratch and scuff resistance. Attractive, even coverage with no drips



(standard on 12-step to 15-step models) The top platform on models 12-step and taller is surrounded on three sides by a 4' high toeboard. Can be added as an option to smaller size models. (WO5)

OPTIONS & ACCESSORIES





models. Accessory #W03

GSW SERIES



GSW2405

Handrail & Outrigger (accessory)

Required when local codes require 3:1 height to base ratio.

5 Step (16" Wide Only) GRCAL05EC-B 5-9 Step GRCAL0509-B 10-12 Step GRCAL1012-B 13-15 Step GRCAL1315-B **GSX SERIES** 3-7 Step (16" Wide Only) GRCAL05EC-O 4-9 Step GECAL0509-O 10-12 Step GRCAL1012-0 13-15 Step GRCAL1315-0



GSW REPLACEMENT PARTS

MODEL	DESCRIPTION	SIZE
999844A	Step Lock Spring	6'-15'
601054A	2" Rubber Pad	6'-15'
921016	Caster	1'-5'
999928A	Front Crutch Tip	1'-5'
999928B	Back Crutch Tip	1'-5'
921004A	4" Swivel Caster	6'-15'
921007A	4" Rigid Caster w/Stud	6'-15'

^{*}GSW parts are not interchangeable with SW parts



