Seating Color Selector

Notes: All the colors are available below with no upcharge. The highlighted colors are available at checkout. To order a non-highlighted color, please call us at 1-855-786-7667 or chat or email us at sales@storemorestore.com. Colors are subject to change without notice.



Xtreme











Note: Photographic fabric scans are not color accurate. Always request actual fabric samples before ordering.

Technical information

X2

Composition 100% Recycled Flame Retardant Polyester.

Retardant Polyester.
Non metallic dyestuffs.

Environmental

Made from 100% recycled polyester. Certified to the EU Ecolabel.

Width

54 inches minimum

Weight

 $9^{1/4}$ oz/sq yd $\pm 5\%$ (14 oz/running yard $\pm 5\%$)

Abrasion Resistance

Meets the ACT Standard for Heavy Duty Upholstery (ASTM D4157 Wyzenbeek method) 100,000 Martindale cycles (BS EN ISO 12947-2:1999) Covered by a comprehensive 5 year wear warranty (full details available)

Flammability

California Technical
Bulletin 117, Section E
UFAC Class 1
BS 7176: 2007 Low
Hazard
BS 7176: 2007 Medium
Hazard
Note: Flammability
performance is dependent
on foam used.

Light Fastness

AATCC-16 (40 hours)

Fastness to Rubbing AATCC-8 (Dry: 4 minimum, Wet: 3 minimum)

Cleaning

Please note that seam performance is dependent on seam construction and needle and thread type. We recommend that appropriate sewing advice be taken.

Note: Batch to batch variations in shade may occur within commercial tolerances. We reserve the right to alter technical specifications without notice. The Unregistered Design Rights and the Copyright in all designs are the exclusive property of Camira Fabrics Limited.

Xtreme

Composition 100% Recycled Flame

100% Recycled Flame Retardant Polyester. Non metallic dyestuffs.

Environmental

Made from 100% recycled polyester. Certified to the EU Ecolabel.

Width

54 inches minimum

Weight

 $9^{1/4}$ oz/sq yd ±5% (14 oz/running yard ±5%)

Abrasion Resistance

Abrasion Resistance
Meets the ACT Standard
for Heavy Duty Upholstery
(ASTM D4157 Wyzenbeek
method)
100,000 Martindale cycles
(BS EN ISO 12947-2:1999)
Covered by a
comprehensive 10 year
wear warranty
(full details available)

Flammability

California Technical Bulletin 117, Section E UFAC Class 1 BS 7176 : 2007 Low Hazard BS 7176 : 2007 Medium Hazard Note: Flammability performance is dependent on foam used.

Light Fastness

AATCC-16 (40 hours)

Fastness to Rubbing AATCC-8 (Dry: 4 minimum, Wet: 3 minimum)

Cleaning

Please note that seam performance is dependent on seam construction and needle and thread type. We recommend that appropriate sewing advice be taken.

Note: Batch to batch variations in shade may occur within commercial tolerances. We reserve the right to alter

notice. The Unregistered Design Rights and the Copyright in all designs are the exclusive property of Camira Fabrics Limited.